

# SAFETY DATA SHEET



## 04100 – SPIRIT LIQUID WAX FLOOR POLISH

Trust Hygiene Services Limited

### 1. IDENTIFICATION OF THE PREPARATION AND COMPANY

**PRODUCT CODE:** 04100  
**PRODUCT NAME:** SPIRIT LIQUID WAX FLOOR POLISH 2 x 5 Ltr  
**DISTRIBUTOR:** Trust Hygiene Services Limited Telephone: 0370 3500 988  
 Sutherland Avenue Fax: 01902 872289  
 Wolverhampton Email: sales@trusthygiene.co.uk  
 West Midlands, WV2 2JH

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
ALIPHATIC DISTILLATE	265-150-3	Xn;R65, R10,R66	60>100%

The full text for all R-Phrases are displayed in Section 16

### 3. HAZARDS IDENTIFICATION

R10 Flammable. R66 Repeated exposure may cause skin dryness or cracking.

### 4. FIRST AID MEASURES

**INHALATION:** Move the exposed person to fresh air at once. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.  
**INGESTION:** DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!  
**SKIN:** Remove affected person from source of contamination. Remove contaminated clothing. Get medical attention if Irritation persists after washing.  
**EYES:** Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

### 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Fire can be extinguished using:., Foam, Dry chemicals, sand, dolomite etc.  
**SPECIAL FIRE FIGHTING PROCEDURES:** Avoid breathing in vapours. Cool containers exposed to flames with water until well after the fire is out. Emits combustible gases if heated. Be aware of danger for fire to re-start.

### 6. ACCIDENTAL RELEASE MEASURES

**SPILL CLEAN UP METHODS:** Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate Clean-up personnel should use respiratory and / or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.  
**ENVIRONMENTAL PERCAUTIONS:** Any spillage needs to be contained and not allowed to enter water courses.

### 7. HANDLING AND STORAGE

**USAGE PRECAUTIONS:** Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.  
**STORAGE PRECAUTIONS:** Flammable / combustible – Keep away from oxidizers, heat and flames. Store in tightly closed original container in a dry, cool and well ventilated place. Keep in original container.  
**USAGE DESCRIPTION:** Flammable liquid storage.

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

#### PROTECTIVE EQUIPMENT:



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>APPEARANCE:</b>	Opaque, Liquid
<b>COLOUR:</b>	Orange
<b>ODOUR:</b>	Hydrocarbon, Solvent
<b>BOILING POINT (°C):</b>	> 160
<b>DENSITY/SPECIFIC GRAVITY (g/ml):</b>	0.78
<b>VAPOUR DENSITY (air=1):</b>	> 1
<b>pH-VALUE, CONC. SOLUTION:</b>	N/A
<b>SOLUBILITY:</b>	Immiscible with water
<b>FLASH POINT (°C):</b>	> 40                      CC (Closed)
<b>FLAMMABILITY LIMIT – LOWER (%):</b>	0.6
<b>FLAMMABILITY LIMIT – UPPER (%):</b>	8

## 10. STABILITY AND REACTIVITY

<b>STABILITY:</b>	Stable under normal temperature conditions.
<b>CONDITIONS TO AVOID:</b>	Avoid heat. Avoid contact with oxidizer or reducing agents.
<b>HAZARDOUS COMPOSITION PRODUCTS:</b>	Fire creates:, Toxic gases / vapours / fumes of:, Carbon monoxide (CO). Carbon dioxide (CO2).

## 11. TOXICOLOGY INFORMATION

<b>INHALATION:</b>	Vapours may cause headache, fatigue, dizziness and nausea.
<b>INGESTION:</b>	Liquid irritates mucous membranes and may cause adnominal pain if swallows.
<b>SKIN CONTACT:</b>	Prolonged or repeated exposure may cause severe irritation.
<b>EYE CONTACT:</b>	Spray and vapour in the eyes may cause irritation and smarting.

## 12. ECOLOGICAL INFORMATION

<b>ECOTOXICITY:</b>	Not classed as Hazardous to the Environment, but release to the environment should be avoided.
---------------------	--

## 13. DISPOSAL CONSIDERATIONS

<b>DISPOSABLE METHODS:</b>	Dispose of waste and residues in accordance with local authority requirements.
----------------------------	--

## 14. TRANSPORT INFORMATION

### **LABEL FOR CONVEYANCE:**



<b>UN NO. ROAD:</b>	1993	<b>UN NO. SEA:</b>	1993
<b>UK ROAD PACK GR.:</b>	III	<b>IMDG CLASS:</b>	3
<b>ADR CLASS NO.:</b>	3	<b>UN NO. AIR:</b>	1993
<b>ADR CLASS:</b>	Class 3: Flammable liquids		
<b>PROPER SHIPPING NAME I:</b>	FLAMMABLE LIQUID NOS (Aliphatic hydrocarbons)		

## 15. REGULATORY INFORMATION

<b>RISK PHRASES:</b>	R10    Flammable. R66    Repeated exposure may cause skin dryness or cracking.
<b>SAFETY PHRASES:</b>	S2    Keep out of the reach of children. S37    Wear suitable gloves S46    If swallowed, seek medical advise immediately and show container or label. S51    Use only in well-ventilated areas
<b>STATUTORY INSTRUMENTS:</b>	Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations.
<b>APPROVED CODE OF PRACTICE:</b>	Classification and Labeling of Substances and Preparations Dangerous for Supply.
<b>GUIDANCE NOTES:</b>	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

## 16. OTHER INFORMATION

<b>USER NOTES:</b>	The following risk phrases relate to the raw materials in the product and not the product itself:
<b>R-PHRASES (Full Text):</b>	R10    Flammable R66    Repeated exposure may cause skin dryness or cracking. R65    Harmful: may cause lung damage if swallowed.
<b>DATE CREATED:</b>	January 2009