

SAFETY DATA SHEET



04100 – SPIRIT LIQUID WAX FLOOR POLISH

Trust Hygiene Services Limited

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT CODE:	04100		
PRODUCT NAME:	SPIRIT LIQUID WAX FLOOR POLISH		5 Ltr
MANUFACTURER:	Trust Hygiene Services Limited	Telephone:	0370 3500 988
	Sutherland Avenue	Fax:	01902 872289
	Wolverhampton	Email:	sales@trusthygiene.co.uk
	West Midlands, WV2 2JH		

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
ALIPHATIC DISTILLATE	265-150-3	Xn;R65, R10,R66	60>100%

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

R10 Flammable. R66 Repeated exposure may cause skin dryness or cracking.

4. FIRST AID MEASURES

INHALATION: Move the exposed person to fresh air at once. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.

INGESTION: DO NOT INDUCE VOMITING! Remove victim immediately from source of exposure. Rinse mouth thoroughly. Provide rest, warmth and fresh air. Get medical attention immediately!

SKIN: Remove affected person from source of contamination. Remove contaminated clothing. Get medical attention if Irritation persists after washing.

EYES: Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Contact physician if irritation persists.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Fire can be extinguished using:., Foam, Dry chemicals, sand, dolomite etc.

SPECIAL FIRE FIGHTING PROCEDURES: Avoid breathing in vapours. Cool containers exposed to flames with water until well after the fire is out. Emits combustible gases if heated. Be aware of danger for fire to re-start.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS: Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate Clean-up personnel should use respiratory and / or liquid contact protection. Absorb in vermiculite, dry sand or earth and place into containers.

ENVIRONMENTAL PERCAUTIONS: Any spillage needs to be contained and not allowed to enter water courses.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Avoid spilling, skin and eye contact. Keep away from heat, sparks and open flame. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level. Use explosion proof electric equipment.

STORAGE PRECAUTIONS: Flammable / combustible – Keep away from oxidizers, heat and flames. Store in tightly closed original container in a dry, cool and well ventilated place. Keep in original container.

USEAGE DESCRIPTION: Flammable liquid storage.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:



9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Opaque, Liquid
COLOUR:	Orange
ODOUR:	Hydrocarbon, Solvent
BOILING POINT (°C):	> 160
DENSITY/SPECIFIC GRAVITY (g/ml):	0.78
VAPOUR DENSITY (air=1):	> 1
pH-VALUE, CONC. SOLUTION:	N/A
SOLUBILITY:	Immiscible with water
FLASH POINT (°C):	> 40 CC (Closed)
FLAMMABILITY LIMIT – LOWER (%):	0.6
FLAMMABILITY LIMIT – UPPER (%):	8

10. STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperature conditions.
CONDITIONS TO AVOID:	Avoid heat. Avoid contact with oxidizer or reducing agents.
HAZARDOUS COMPOSITION PRODUCTS:	Fire creates:, Toxic gases / vapours / fumes of:, Carbon monoxide (CO). Carbon dioxide (CO2).

11. TOXICOLOGY INFORMATION

INHALATION:	Vapours may cause headache, fatigue, dizziness and nausea.
INGESTION:	Liquid irritates mucous membranes and may cause adnominal pain if swallows.
SKIN CONTACT:	Prolonged or repeated exposure may cause severe irritation.
EYE CONTACT:	Spray and vapour in the eyes may cause irritation and smarting.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:	Not classed as Hazardous to the Environment, but release to the environment should be avoided.
---------------------	--

13. DISPOSAL CONSIDERATIONS

DISPOSABLE METHODS:	Dispose of waste and residues in accordance with local authority requirements.
----------------------------	--

14. TRANSPORT INFORMATION

LABEL FOR CONVEYANCE:



UN NO. ROAD:	1993	UN NO. SEA:	1993
UK ROAD PACK GR.:	III	IMDG CLASS:	3
ADR CLASS NO.:	3	UN NO. AIR:	1993
ADR CLASS:	Class 3: Flammable liquids		
PROPER SHIPPING NAME I:	FLAMMABLE LIQUID NOS (Aliphatic hydrocarbons)		

15. REGULATORY INFORMATION

RISK PHRASES:	R10 Flammable. R66 Repeated exposure may cause skin dryness or cracking.
SAFETY PHRASES:	S2 Keep out of the reach of children. S37 Wear suitable gloves S46 If swallowed, seek medical advise immediately and show container or label. S51 Use only in well-ventilated areas
STATUTORY INSTRUMENTS:	Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE:	Classification and Labeling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION

USER NOTES:	The following risk phrases relate to the raw materials in the product and not the product itself:
R-PHRASES (Full Text):	R10 Flammable R66 Repeated exposure may cause skin dryness or cracking. R65 Harmful: may cause lung damage if swallowed.
DATE CREATED:	January 2009