

SAFETY DATA SHEET


09000 / 09010 / 90303 / 09050 – BREEZE AIR FRESHENER
Trust Hygiene Services Limited

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT CODE / NAME:	09000 (K214)	BREEZE ALPINE AIR FRESHENER	400 ml
	09010 (K212)	BREEZE SPRINGTIME AIR FRESHENER	400 ml
	09030 (K122)	BREEZE POT POURRI AIR FRESHENER	400 ml
	09050 (K213)	BREEZE SUNFLOWER AIR FRESHENER	400 ml

DISTRIBUTOR:	Trust Hygiene Services Limited	Telephone:	0370 3500 988
	Sutherland Avenue	Fax:	01902 872289
	Wolverhampton	Email:	sales@trusthygiene.co.uk
	West Midlands		
	WV2 2JH		

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
BUTANE	203-448-7	F+;R12	10-30%
PROPAN-2-OL	200-661-7	R;R11 Xi;R36 R67	1-5%

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

R12 Extremely Flammable.

PRESSUREISED COANTAINER – increase temperature greater that 50°C will cause internal pressure to rise potentially causing bursting / explosion.

4. FIRST AID MEASURES

INHALATION:	Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.
INGESTION:	Rinse mouth thoroughly. Drink plenty of water. Get medical attention.
SKIN:	Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
EYES:	Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:	Use:, Powder, Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
SPECIAL FIRE FIGHTING PROCEDURES:	Containers close to fire should be removed or cooled with water. Use water to keep exposed containers cool and disperse vapours.
UNUSUAL FIRE & EXPLOSIVE HAZARDS:	Aerosol cans may explode in a fire.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS:	Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, heat and smoking. Ventilate if leakage cannot be stopped, evacuate area.
ENVIRONMENTAL PRECAUTIONS:	Any spillage needs to be contained and not allowed to enter water courses

7. HANDLING AND STORAGE

USAGE PRECAUTIONS:	Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use appropriate respirator if air contamination is above accepted level.
STORAGE PRECAUTIONS:	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXT 15 Min
BUTANE		WEL	1450 mg/m3	1450 mg/m3

PROTECTIVE EQUIPMENT:

9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Aerosol
PHYSICAL DATA COMMENTS:	Information given relates to total aerosol container contents
FLASH POINT (°C):	- 74 N/A
AUTO IGNITION TEMPERATURE (°C):	+ 405
FLAMMABILITY LIMIT – LOWER (%):	1.8
FLAMMABILITY LIMIT – UPPER (%):	10.0

10. STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperature conditions.
CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition. Increase in temperature to greater than 50 degrees will cause rise in internal pressure with likelihood of bursting / explosion
HAZARDOUS COMPOSITION PRODUCTS:	Fire creates:, Toxic gases / vapours / fumes of:, Carbon monoxide (CO). Carbon dioxide (CO2).

11. TOXICOLOGY INFORMATION

INHALATION:	High concentrations of vapours may irritate respiratory system and lead to headache, fatigue, nausea and vomiting. Gas or vapour displaces oxygen available for breathing (asphyxiate). Unconsciousness.
SKIN CONTACT:	No specific health warnings noted.
EYE CONTACT:	Irritation of eyes and mucous membranes.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:	Not regarded as dangerous for the environment.
---------------------	------------------------------------------------

13. DISPOSAL CONSIDERATIONS

DISPOSABLE METHODS:	Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.
----------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------

14. TRANSPORT INFORMATION

UN NO. ROAD:	1950
UK ROAD TRANSPORT CLASS:	2
ADR CLASS NO.:	2
PROPER SHIPPING NAME I:	AEROSOLS, FLAMMABLE
UN NO. SEA:	1950
IMDG CLASS:	2.1
UN NO. AIR:	1950
ICAO CLASS:	2.1

15. REGULATORY INFORMATION

LABEL FOR SUPPLY:



RISK PHRASES:	R12 Extremely flammable.
SAFETY PHRASES:	S2 Keep out of the reach of children S16 Keep away from sources of ignition – No Smoking S51 Use only in well-ventilated areas.
STATUTORY INSTRUMENTS:	Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE:	Classification and Labeling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION

USER NOTES:	The following risk phrases relate to the raw materials in the product and not the product itself:
R-PHRASES (Full Text):	R12 Extremely flammable. R11 Highly flammable. R69 Irritation to eyes. R67 Vapours may cause drowsiness and dizziness.
DATE CREATED:	January 2009