

SAFETY DATA SHEET



09100 – SELKILL FLY SPRAY

Trust Hygiene Services Limited

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

| | | | |
|----------------------|--|------------------------------|---|
| PRODUCT CODE: | 09100 | | |
| PRODUCT NAME: | SELKILL FLY SPRAY | | 480 ml |
| DISTRIBUTOR: | Trust Hygiene Services Limited Sutherland Avenue Wolverhampton West Midlands WV2 2JH | Telephone: Fax: Email: | 0370 3500 988 01902 872289 sales@trusthygiene.co.uk |

2. COMPOSITION/INFORMATION ON INGREDIENTS

| NAME | EINECS Nr.: | CLASSIFICATION | CONTENT |
|--------------------|-------------|-----------------------------------|---------|
| BUTANE | 203-448-7 | F+;R12 | 30-60% |
| PERMETHRIN | 258-067-9 | Xn;R20/22 R43 N;R50/53 | < 0.5% |
| PIPERONYL BUTOXIDE | 200-076-7 | T;R23/24/25. Carc 3;R40. N;R51/53 | 1-5% |
| PROPAN-2-OL | 200-661-7 | F;R11 Xi;R36 R67 | 5-10% |
| TETRAMETHRIN | 231-711-6 | Xi;R36. N;R50/53 | < 0.5% |

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

R12 Extremely Flammable.
R40 Limited evidence of a carcinogenic effect.
R51/53 Very Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

PRESSUREISED COANTAINER – increase temperature greater that 50°C will cause internal pressure to rise potentially causing bursting / explosion.

4. FIRST AID MEASURES

INHALATION: Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention.
INGESTION: Rinse mouth thoroughly. Drink plenty of water. Get medical attention.
SKIN: Wash the skin immediately with soap and water. Get medical attention if any discomfort continues.
EYES: Spray in the eyes:, Promptly was eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Use:, Powder, Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
SPECIAL FIRE FIGHTING PROCEDURES: Containers close to fire should be removed or cooled with water. Use water to keep exposed containers cool and disperse vapours.
UNUSUAL FIRE & EXPLOSIVE HAZARDS: Aerosol cans may explode in a fire.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS: Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate if leakage cannot be stopped, evacuate area.
ENVIRONMENTAL PERCAUTIONS: Any spillage needs to be contained and not allowed to enter water courses.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS: Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use appropriate respirator if air contamination is above accepted level.
STORAGE PRECAUTIONS: Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

| INGREDIENT NAME: | CAS No.: | STD | LT EXP 8 Hrs | ST EXP 15 Min |
|------------------|----------|-----|--------------|---------------|
| BUTANE | | WEL | 1450 mg/m3 | 1810 mg/m3 |

PROTECTIVE EQUIPMENT:



9. PHYSICAL AND CHEMICAL PROPERTIES

| | |
|---------------------------------|--|
| APPEARANCE: | Aerosol |
| PHYSICAL DATA COMMENTS: | Information given relates to total aerosol container contents. |
| FLASH POINT (°C): | -74 N/A |
| AUTO IGNITION TEMPERATURE (°C): | + 405 |
| FLAMMABILITY LIMIT – LOWER (%): | 1.8 |
| FLAMMABILITY LIMIT – UPPER (%): | 10.0 |

10. STABILITY AND REACTIVITY

| | |
|---------------------------------|--|
| STABILITY: | Stable under normal temperature conditions. |
| CONDITIONS TO AVOID: | Avoid heat, flames and other sources of ignition. |
| HAZARDOUS COMPOSITION PRODUCTS: | Fire creates:, Toxic gases / vapours / fumes of:, Carbon monoxide (CO). Carbon dioxide (CO2). |

11. TOXICOLOGY INFORMATION

| | |
|---------------|---|
| INHALATION: | May cause irritation to respiratory system. Vapours may cause headache, fatigue, dizziness and nausea. Prolonged inhalation of high concentrations may damage respiratory system. |
| SKIN CONTACT: | Prolonged or repeated exposure may cause severe irritation. Acts as a defatting agent on skin. |
| EYE CONTACT: | May cause cracking of skin, and eczema. Irritation of eyes and mucous membranes. |

12. ECOLOGICAL INFORMATION

| | |
|--------------|---|
| ECOTOXICITY: | Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. |
|--------------|---|

13. DISPOSAL CONSIDERATIONS

| | |
|---------------------|---|
| DISPOSABLE METHODS: | Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements. |
|---------------------|---|

14. TRANSPORT INFORMATION

| | |
|--------------------------|---------------------|
| UN NO. ROAD: | 1950 |
| UK ROAD TRANSPORT CLASS: | 2 |
| ADR CLASS NO.: | 2 |
| PROPER SHIPPING NAME I: | AEROSOLS, FLAMMABLE |
| UN NO. SEA: | 1950 |
| IMDG CLASS: | 2.1 |
| UN NO. AIR: | 1950 |
| ICAO CLASS: | 2.1 |

15. REGULATORY INFORMATION

LABEL FOR SUPPLY:



RISK PHRASES:

R12 Extremely flammable.
R40 Limited evidence of a carcinogenic effect.
R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

SAFETY PHRASES:

S16 Keep away from sources of ignition – No Smoking
S23 Do no breath vapour/spray.
P14 Contains PERMETHRIN. May produce an allergic reaction,
S2 Keep out of the reach of children

STATUTORY INSTRUMENTS:

Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations.

APPROVED CODE OF PRACTICE:

Classification and Labeling of Substances and Preparations Dangerous for Supply.

GUIDANCE NOTES:

Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION

USER NOTES:

The following risk phrases relate to the raw materials in the product and not the product itself:

R-PHRASES (Full Text):

R12 Extremely flammable
R11 Highly Flammable
R36 Irritating to eyes
R67 Vapours may cause drowsiness and dizziness.
R20/22 Harmful by inhalation and if swallowed.
R43 May cause sensitisation by skin contact.
R50/53 Very toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment.
R23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
R40 Limited evidence of a carcinogenic effect.

DATE CREATED:

January 2009