

SAFETY DATA SHEET



09110 – SELFREEZE CHEWING GUM REMOVER

Trust Hygiene Services Limited

1. IDENTIFICATION OF THE PREPARATION AND COMPANY

PRODUCT CODE:	09110		
PRODUCT NAME:	SELFREEZE CHEWING GUM REMOVER		340 gm
DISTRIBUTOR:	Trust Hygiene Services Limited Sutherland Avenue Wolverhampton West Midlands WV2 2JH	Telephone: Fax: Email:	0370 3500 988 01902 872289 sales@trusthygiene.co.uk

2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
PENTANE	203-692-4	F+;R12 Xn;R65 R66 R67 N;R51/53	10-30%

The full text for all R-Phrases are displayed in Section 16

3. HAZARDS IDENTIFICATION

R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

PRESSUREISED COANTAINER – increase temperature greater that 50°C will cause internal pressure to rise potentially causing bursting / explosion.

4. FIRST AID MEASURES

INHALATION:	Move the exposed person to fresh air at once. Keep the affected person warm and at rest. Get prompt medical attention. For breathing difficulties oxygen may be necessary.
INGESTION:	Rinse mouth thoroughly. Drink plenty of water. Get medical attention.
SKIN:	Rinse with water. Get medical attention if any discomfort continues.
EYES:	Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA:	Use:, Powder, Dry chemicals, sand, dolomite etc. Water spray, fog or mist.
SPECIAL FIRE FIGHTING PROCEDURES:	Containers close to fire should be removed or cooled with water. Use water to keep exposed containers cool and disperse vapours.
UNUSUAL FIRE & EXPLOSIVE HAZARDS:	Aerosol cans may explode in a fire.

6. ACCIDENTAL RELEASE MEASURES

SPILL CLEAN UP METHODS:	Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames, heat and smoking. Ventilate if leakage cannot be stopped, evacuate area.
ENVIRONMENTAL PERCAUTIONS:	Any spillage needs to be contained and not allowed to enter water courses.

7. HANDLING AND STORAGE

USAGE PRECAUTIONS:	Keep away from heat, sparks and open flame. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use appropriate respirator if air contamination is above accepted level.
STORAGE PRECAUTIONS:	Aerosol cans: Must not be exposed to direct sunlight or temperatures above 50°C.

8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

PROTECTIVE EQUIPMENT:



9. PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	Aerosol
COLOUR:	Colourless
ODOUR:	Almost odourless
PHYSICAL DATA COMMENTS:	Information given relates to total aerosol container contents.
DENSITY / SPECIFIC GRAVITY (g/ml):	1.1
VOLATILE BY VOL. (%):	100

10. STABILITY AND REACTIVITY

STABILITY:	Stable under normal temperature conditions. Avoid: Shocks and physical damage.
CONDITIONS TO AVOID:	Avoid heat, flames and other sources of ignition.
HAZARDOUS COMPOSITION PRODUCTS:	Fire creates:, Toxic gases / vapours / fumes of:, Carbon monoxide (CO). Carbon dioxide (CO2).

11. TOXICOLOGY INFORMATION

INHALATION:	High concentrations of vapour even for short periods must be avoided since this may be dangerous and cause unconsciousness and prove suddenly fatal.
SKIN CONTACT:	Contact with liquid will cause freezing of body tissue and frostbite.
EYE CONTACT:	Irritation is likely. Contact with liquid causes freezing of body tissue and frostbite.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:	Because produce is so volatile if it is released into the environment the liquid would very quickly turn into vapour.
---------------------	---

13. DISPOSAL CONSIDERATIONS

DISPOSABLE METHODS:	Empty containers must not be burned because of explosion hazard. Dispose of waste and residues in accordance with local authority requirements.
----------------------------	---

14. TRANSPORT INFORMATION

LABEL FOR CONVEYANCE:



UN NO. ROAD:	1950	UN NO. SEA:	1950
UK ROAD TRANSPORT CLASS:	2.2	IMDG CLASS:	2.1
ADR CLASS NO.:	2.2	UN NO. AIR:	1950
ADR CLASS:	Class 2: Gases	ICAO CLASS:	2.1
PROPER SHIPPING NAME I:	AEROSOLS, ASPHYXIANT		

15. REGULATORY INFORMATION

RISK PHRASES:	R52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
SAFETY PHRASES:	S2 Keep out of the reach of children S24/25 Avoid contact with skin and eyes. S51 Use only in well-ventilated areas. S23 Do no breath vapour/spray.
STATUTORY INSTRUMENTS:	Control of Substances Hazardous to Health. Chemicals (Hazard Information and Packaging) Regulations.
APPROVED CODE OF PRACTICE:	Classification and Labeling of Substances and Preparations Dangerous for Supply.
GUIDANCE NOTES:	Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

16. OTHER INFORMATION

USER NOTES:	The following risk phrases relate to the raw materials in the product and not the product itself:
R-PHRASES (Full Text):	R12 Extremely flammable R51/53 Toxic to aquatic organisms, may cause long term adverse effects in the aquatic environment. R66 Repeated exposure may cause skin dryness or cracking. R67 Vapours may cause drowsiness and dizziness. R65 Harmful: may cause lung damage if swallowed.
DATE CREATED:	January 2009