

# SAFETY DATA SHEET



## 09410 – SELECT WAX FREE POLISH

Trust Hygiene Services Limited

### 1. IDENTIFICATION OF THE PREPARATION AND COMPANY

**PRODUCT CODE:** 09410

**PRODUCT NAME:** SELECT WAX FREE POLISH – TRIGGER SPRAY 750 ml

**DISTRIBUTOR:** Trust Hygiene Services Limited Telephone: 0370 3500 988  
Sutherland Avenue Fax: 01902 872289  
Wolverhampton Email: sales@trusthygiene.co.uk  
West Midlands  
WV2 2JH

### 2. COMPOSITION/INFORMATION ON INGREDIENTS

NAME	EINECS Nr.:	CLASSIFICATION	CONTENT
ALIPHATIC DISTILLATE	265-150-3	Xn;R65 R10,R66	5-10%
PROPAN-2-OL	200-661-7	F;R11 Xi;R36 67	5-10%

The full text for all R-Phrases are displayed in Section 16

### 3. HAZARDS IDENTIFICATION

Not regarded as a health or environment hazard under current legislation.

### 4. FIRST AID MEASURES

**INGESTION:** DO NOT INDUCE VOMITING!, Rinse mouth thoroughly. Drink plenty of water. Get medical attention.

**SKIN:** Rinse with water. Get medical attention if any discomfort continues

**EYES:** Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes. Get medical attention if any discomfort continues.

### 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** This product is not flammable. Use fire-extinguishing media appropriate for surrounding materials.

### 6. ACCIDENTAL RELEASE MEASURES

**SPILL CLEAN UP METHODS:** Stop leak if possible without risk. Absorb in vermiculite, dry sand or earth and place into containers. Flush with plenty of water to clean spillage area. Do not contaminate water courses or sewer.

**ENVIRONMENTAL PRECAUTIONS:** Any spillage needs to be contained and not allowed to enter water courses.

### 7. HANDLING AND STORAGE

**USAGE PRECAUTIONS:** Eye protection should be considered where there is a risk of splashing. Rubber gloves and barrier cream are recommended when using any chemical.

**STORAGE PRECAUTIONS:** Store in tightly closed original container in a dry, cool and well-ventilated place. Keep in original container.

### 8. EXPOSURE CONTROLS AND PERSONAL PROTECTION

INGREDIENT NAME:	CAS No.:	STD	LT EXP 8 Hrs	ST EXT 15 Min
PROPAN-2-OL		WEL	999 mg/m <sup>3</sup>	1250 mg/m <sup>3</sup>

**PROTECTIVE EQUIPMENT:**



## **9. PHYSICAL AND CHEMICAL PROPERTIES**

**APPEARANCE:** Liquid  
**COLOUR:** White / off white  
**ODOUR:** Perfume sent  
**BOILING POINT (°C):** 100  
**DENSITY / SPECIFIC GRAVITY (g/ml):** 0.955 - 0965  
**pH-VALUE, CONC. SOLUTION:** 7.0  
**SOLUBILITY:** Forms an emulsion with water.

## **10. STABILITY AND REACTIVITY**

**STABILITY:** Stable under normal temperature conditions.  
**CONDITIONS TO AVOID:** Avoid excess heat for prolonged periods of time.  
**HAZ. COMPOSITION PRODUCTS:** Not Known

## **11. TOXICOLOGY INFORMATION**

**INGESTION:** Liquid irritates mucous membranes and may cause abdominal pain if swallowed. Diarrhoea.  
Nausea, vomiting.  
**SKIN CONTACT:** Prolonged contact may cause dryness of the skin.  
**EYE CONTACT:** Irritation is likely.

## **12. ECOLOGICAL INFORMATION**

**ECOTOXICITY:** Not classed as hazardous to the environment but release to the environment should be avoided.

## **13. DISPOSAL CONSIDERATIONS**

**DISPOSABLE METHODS:** Dispose of waste and residues in accordance with local authority requirements.

## **14. TRANSPORT INFORMATION**

**ROAD TRANSPORT NOTES:** Not Classified  
**RAIL TRANSPORT NOTES:** Not Classified  
**SEA TRANSPORT NOTES:** Not Classified  
**AIR TRANSPORT NOTES:** Not Classified

## **15. REGULATORY INFORMATION**

**RISK PHRASES:** NC Not classified.  
**SAFETY PHRASES:** S2 Keep out of the reach of children  
**STATUTORY INSTRUMENTS:** Chemicals (Hazard Information and Packaging) Regulations.  
**APPROVED CODE OF PRACTICE:** Classification and Labeling of Substances and Preparations Dangerous for Supply.  
**GUIDANCE NOTES:** Workplace Exposure Limits EH40. Introduction to Local Exhaust Ventilation HS(G)37. CHIP for everyone HSG(108).

## **16. OTHER INFORMATION**

**USER NOTES:** The following risk phrases relate to the raw materials in the product and not the product itself:  
**R-PHRASES (Full Text):** R11 Highly flammable.  
R36 Irritating to eyes  
R67 Vapours may cause drowsiness and dizziness.  
R10 Flammable  
R66 Repeated exposure may cause skin dryness or cracking  
R65 Harmful: may cause lung damage if swallowed.  
**DATE CREATED:** January 2009