



SHADES - CITRUS SQUEEZE (MD)

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Date of issue: 12/02/2016

Revision date: 01/01/2017

Version: 10.0

SHADES - CITRUS SQUEEZE (MD)

KSD3

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : SHADES - CITRUS SQUEEZE (MD)
Product code : 09000
Type of product : Aerosol
Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use
Industrial/Professional use spec : For professional use only
Use of the substance/mixture : Air Freshener

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Trust Hygiene Services Limited, Principle House, Leamore Lane, Bloxwich, Walsall, West Midlands, WS2 7PS

Email: sales@trusthygiene.co.uk www.trusthygiene.com
Telephone: 0370 3500 966

Emergency Numbers: M-F 09.00 - 17.00 (0370 3500 988) Outside of office hours, please call NHS Direct on 111

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol 1 H222;H229
Eye Irrit. 2 H319
Skin Sens. 1 H317
Aquatic Chronic 2 H411

Full text of H-phrases: see section 16

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS07

GHS09

Signal word (CLP) :

Danger

Hazardous ingredients :

(R)-p-mentha-1,8-diene, d-limonene

Hazard statements (CLP) :

H222 - Extremely flammable aerosol
H229 - Pressurised container: May burst if heated
H317 - May cause an allergic skin reaction
H319 - Causes serious eye irritation
H411 - Toxic to aquatic life with long lasting effects

Precautionary statements (CLP) :

P102 - Keep out of reach of children
P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
P211 - Do not spray on an open flame or other ignition source
P251 - Do not pierce or burn, even after use
P261 - Avoid breathing spray
P264 - Wash hands thoroughly after handling
P272 - Contaminated work clothing should not be allowed out of the workplace
P273 - Avoid release to the environment
P280 - Wear eye protection
P302+P352 - IF ON SKIN: Wash with plenty of soap, water
P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

Safety Data Sheet

according to Regulation (EC) No. 453/2010

contact lenses, if present and easy to do. Continue rinsing
 P363 - Wash contaminated clothing before reuse
 P333+P313 - If skin irritation or rash occurs: Get medical advice/attention
 P337+P313 - If eye irritation persists: Get medical advice/attention
 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients**3.1. Substance**

Not applicable

3.2. Mixture

Name	Product identifier	%	Classification according to Directive 67/548/EEC	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane substance with national workplace exposure limit(s) (DK, GB, IE)	(CAS No) 106-97-8 (EC no) 203-448-7 (EC index no) 601-004-00-0	30 - 60	F+; R12	Flam. Gas 1, H220 Press. Gas
propane substance with national workplace exposure limit(s) (DK, IE)	(CAS No) 74-98-6 (EC no) 200-827-9 (EC index no) 601-003-00-5	15 - 30	F+; R12	Flam. Gas 1, H220
propan-2-ol, isopropyl alcohol, isopropanol	(CAS No) 67-63-0 (EC no) 200-661-7 (EC index no) 603-117-00-0 (REACH-no) 01-2119457558-25	5 - 15	F; R11 Xi; R36 R67	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
(R)-p-mentha-1,8-diene, d-limonene	(CAS No) 5989-27-5 (EC no) 227-813-5 (EC index no) 601-029-00-7	1 - 5	R10 Xi; R38 R43 N; R50/53	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of R- and H-phrases: see section 16

SECTION 4: First aid measures**4.1. Description of first aid measures**

First-aid measures general : Get medical advice/attention if you feel unwell.
 First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing.
 First-aid measures after skin contact : Wash with plenty of soap and water.
 First-aid measures after eye contact : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
 First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Not expected to present a significant hazard under anticipated conditions of normal use.
 Symptoms/injuries after inhalation : May cause respiratory irritation.
 Symptoms/injuries after skin contact : Repeated exposure may cause skin dryness or cracking.
 Symptoms/injuries after eye contact : Causes eye irritation.
 Symptoms/injuries after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures**5.1. Extinguishing media**

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol.
 Explosion hazard : Explosion risk in case of fire.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

General measures : Remove ignition sources.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage**7.1. Precautions for safe handling**

Additional hazards when processed : Pressurized container: Do not pierce or burn, even after use.

Precautions for safe handling : Do not spray on an open flame or other ignition source.

Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Keep away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible products : Oxidizing agent. Strong acids. Strong bases.

Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

propane (74-98-6)		
Denmark	Local name	Propan
Denmark	Grænseværdie (langvarig) (mg/m ³)	1800 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	1000 ppm
Ireland	Local name	Propane
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
Ireland	Notes (IE)	Asphx
propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)		
Denmark	Local name	Isopropylalkohol (2005)
Denmark	Grænseværdie (langvarig) (mg/m ³)	490 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	200 ppm
Germany	TRGS 900 Limitation of exposure peaks (mg/m ³)	1000 mg/m ³
Ireland	Local name	Isopropyl alcohol
Ireland	OEL (8 hours ref) (ppm)	200 ppm
Ireland	OEL (15 min ref) (ppm)	400 ppm
Ireland	Notes (IE)	Sk
Netherlands	Grenswaarde TGG 8H (mg/m ³)	650 mg/m ³
Netherlands	Grenswaarde TGG 15MIN (mg/m ³)	0 mg/m ³
United Kingdom	Local name	Propan-2-ol
United Kingdom	WEL TWA (mg/m ³)	999 mg/m ³
United Kingdom	WEL TWA (ppm)	400 ppm
United Kingdom	WEL STEL (mg/m ³)	1250 mg/m ³

Safety Data Sheet

according to Regulation (EC) No. 453/2010

propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)		
United Kingdom	WEL STEL (ppm)	500 ppm
butane (106-97-8)		
Denmark	Local name	n-Butan
Denmark	Grænseværdie (langvarig) (mg/m ³)	1200 mg/m ³
Denmark	Grænseværdie (langvarig) (ppm)	500 ppm
Ireland	Local name	Butane
Ireland	OEL (8 hours ref) (ppm)	1000 ppm
United Kingdom	Local name	Butane
United Kingdom	WEL TWA (mg/m ³)	1450 mg/m ³
United Kingdom	WEL TWA (ppm)	600 ppm
United Kingdom	WEL STEL (mg/m ³)	1810 mg/m ³
United Kingdom	WEL STEL (ppm)	750 ppm
United Kingdom	Remark (WEL)	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)

8.2. Exposure controls

Materials for protective clothing	: Not required for normal conditions of use
Hand protection	: Protective gloves
Eye protection	: Safety glasses
Skin and body protection	: Not required for normal conditions of use
Respiratory protection	: Not required for normal conditions of use

**SECTION 9: Physical and chemical properties****9.1. Information on basic physical and chemical properties**

Physical state	: Liquid
Appearance	: Aerosol.
Colour	: Colourless.
Odour	: lemon-like.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: No data available
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: 0.6
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 453/2010

SECTION 10: Stability and reactivity**10.1. Reactivity**

Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Direct sunlight. Heat. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information**11.1. Information on toxicological effects**

Acute toxicity	: Not classified
Skin corrosion/irritation	: Not classified
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
Specific target organ toxicity (single exposure)	: Not classified
Specific target organ toxicity (repeated exposure)	: Not classified
Aspiration hazard	: Not classified

SYSTEM 3000 - CITRUS SQUEEZE

Vaporizer	Aerosol
-----------	---------

SECTION 12: Ecological information**12.1. Toxicity****propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)**

LC50 fishes 1	9640 mg/l
EC50 other aquatic organisms 1	13299 mg/l EC50 waterflea (48 h)
EC50 other aquatic organisms 2	> 1000 mg/l IC50 algae (72 h) mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential**propan-2-ol, isopropyl alcohol, isopropanol (67-63-0)**

Log Pow	0.14
---------	------

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations**13.1. Waste treatment methods**

Waste disposal recommendations : Do not pierce or burn, even after use.

SECTION 14: Transport information

In accordance with ADR / RID / IMDG / IATA / ADN

Safety Data Sheet

according to Regulation (EC) No. 453/2010

14.1. UN number

UN-No. (ADR) : 1950
 UN-No. (IMDG) : 1950
 UN-No.(IATA) : 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
 Proper Shipping Name (IMDG) : AEROSOLS
 Proper Shipping Name (IATA) : AEROSOLS, FLAMMABLE
 Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D), ENVIRONMENTALLY HAZARDOUS
 Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1, MARINE POLLUTANT/ENVIRONMENTALLY HAZARDOUS

14.3. Transport hazard class(es)**ADR**

Transport hazard class(es) (ADR) : 2.1
 Danger labels (ADR) : 2.1

**IMDG**

Transport hazard class(es) (IMDG) : 2.1
 Danger labels (IMDG) : 2.1

**IATA**

Transport hazard class(es) (IATA) : 2.1
 Hazard labels (IATA) : 2.1

**14.4. Packing group**

Packing group (ADR) : Not applicable
 Packing group (IMDG) : Not applicable
 Packing group (IATA) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : Yes
 Marine pollutant : Yes
 Other information : No supplementary information available

14.6. Special precautions for user**- Overland transport**

Classification code (ADR) : 5F
 Special provisions (ADR) : 190, 327, 344, 625
 Limited quantities (ADR) : 1L
 Excepted quantities (ADR) : E0
 Packing instructions (ADR) : P207, LP02
 Special packing provisions (ADR) : PP87, RR6, L2

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Mixed packing provisions (ADR)	: MP9
Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV9, CV12
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D

- Transport by sea

Special provisions (IMDG)	: 63, 190, 277, 327, 344, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP02
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None

- Air transport

PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

IBC code	: Not applicable.
----------	-------------------

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****15.1.1. EU-Regulations**

Contains no substances with Annex XVII restrictions
 Contains no substance on the REACH candidate list
 Contains no REACH Annex XIV substances

15.1.2. National regulations**Germany**

VwVwS Annex reference	: Water hazard class (WGK) 3, strongly hazardous to water (Classification according to VwVwS, Annex 4)
12th Ordinance Implementing the Federal Immission Control Act - 12.BImSchV	: Is not subject of the 12. BImSchV (Hazardous Incident Ordinance)

Denmark

Recommendations Danish Regulation	: Young people below the age of 18 years are not allowed to use the product
-----------------------------------	---

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of R-, H- and EUH-phrases:

Aerosol 1	Aerosol, Category 1
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1

Safety Data Sheet

according to Regulation (EC) No. 453/2010

Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Flam. Gas 1	Flammable gases, Category 1
Flam. Liq. 2	Flammable liquids, Category 2
Flam. Liq. 3	Flammable liquids, Category 3
Press. Gas	Gases under pressure
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Sensitisation — Skin, category 1
STOT SE 3	Specific target organ toxicity — Single exposure, Category 3, Narcosis
H220	Extremely flammable gas
H222	Extremely flammable aerosol
H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H229	Pressurised container: May burst if heated
H315	Causes skin irritation
H317	May cause an allergic skin reaction
H319	Causes serious eye irritation
H336	May cause drowsiness or dizziness
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

SDS EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product

Mon - Fri Office 9am-5pm 0370 3500 111 NHS - Out of office hours